

K2 POWER ES 100 K

2-way component kit



Aluminum basket with compact design

- Rigid, antimagnetic and designed for neodymium motor

K2 Power sandwich cone

- Dynamic & precise

Separated compact crossover (Tweeter 0 / +3 / - 3 dB/oct)

- Quick install and easy settings



Tweeter:

3 assembly solutions

- Factory location
- Flush
- In oriented pod

Integrated terminal

- More compact

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKM "M" profile aramid fiber

- inverted dome tweeter
- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- New shape of cone
- High displacement
- Compact crossover

TECHNICAL CHARACTERISTICS

2-way component kit

Diameter: 4" (100mm)

Voice coil diameter: 0^{13/16}" (20mm)

Voice coil height: 0^{1/3}" (8.5mm)

Motor: Neodymium

Tweeter: TKM ("M" profile aramid fiber inverted dome)

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 12/12dB (3.5kHz)

Tweeter Adjustable level: +3; 0; -3dB/oct

Max. power: 120W

Nom. power: 60W RMS

Sensitivity (2.83V/1m): 90dB

Frequency response: 110Hz- 22kHz

Impedance: 4 Ω

Accessories: Supplied grilles



Elite

"HAUTE COUTURE" SOUND



FOCAL

THE SPIRIT OF SOUND