

# K2 POWER ES 130K

## 2-way component kit



### Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

### K2 Power sandwich cone

- Dynamic & precise

### Separated compact crossover (Tweeter 0 / +3 / - 3 dB/oct)

- Quick install and easy settings



### Tweeter: 3 assembly solutions

- Factory location
- Flush
- In oriented pod

### Integrated terminal

More compact

### Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

### TKM "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

## WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- High linearity
- High SPL (for the size)

## TECHNICAL CHARACTERISTICS

### 2-way component kit

**Diameter:** 5" (130mm)

**Voice coil diameter:** 1" (25mm)

**Voice coil height:** 0<sup>1</sup>/<sub>2</sub>" (12mm)

**Motor:** Magnet

**Tweeter:** TKM ["M" profile aramid fiber inverted dome]

**Cone:** Composite K2 Power "W" sandwich cone

**Surround:** Tuned Mass Damper (TMD®)

**Separated crossover:** 6-12/12dB (3.5kHz)

**Tweeter Adjustable level:** +3; 0; -3dB/oct

**Max. power:** 160W

**Nom. power:** 80W RMS

**Sensitivity (2.83V/1m):** 90dB

**Frequency response:** 65Hz- 22kHz

**Impedance:** 4 Ω

**Accessories:** Supplied grilles



**Elite**

"HAUTE COUTURE" SOUND



**FOCAL**

THE SPIRIT OF SOUND