

K2 POWER ES 165KX3

3-way component kit



Aluminum chassis new design

- Rigid, antimagnetic with exclusive design for a better excursion

K2 Power sandwich cone

- Dynamic & precise

Bi-Amp audiophile crossover

- (Tweeter 0 / +3 / - 3 dB/oct), multi settings
- Reliability and power

Aluminum tweeter housing

- Flush "high tech" fitting design



Integrated terminal

- More compact

Exclusive VC venting system

- High SPL and high power handling

Butyl surround exclusive patent "TMD" (Tuned Mass Damper) with S/N engraved

- Better control, more neutral and linear sound

TKMX "M" profile aramid fiber inverted dome tweeter

- High extension in treble
- Smooth and precision

WHAT MAKES THE DIFFERENCE

- Inverted dome "M"-shaped tweeter
- Bi-Amp crossover
- High power handling
- 3" compact medium size
- Aluminum and mesh grille
- Safe impedance

TECHNICAL CHARACTERISTICS

3-way component kit

Diameter: 6 1/4" (165mm)

Voice coil diameter: 1 9/16" (40mm)

Voice coil height: 0 2/3" (16.5mm)

Motor: Magnet

Tweeter: TKMX ("M" profile aramid fiber inverted dome)

Cone: Composite K2 Power "W" sandwich cone

Surround: Tuned Mass Damper (TMD®)

Separated crossover: 6-12/12/12dB

(3/4/500Hz/3.5kHz)

Tweeter Adjustable level: +3; 0; -3dB/oct

Max.power: 240W

Nom.power: 120W RMS

Sensitivity (2.83V/1m): 93dB

Frequency response: 45Hz- 22kHz

Impedance: 4 Ω

Accessories: Supplied grilles and midbox



Elite

"HAUTE COUTURE" SOUND



FOCAL
THE SPIRIT OF SOUND