

 SpeakerCraft®



Ruckus Series


A major upgrade in both aesthetics and performance, Ruckus landscape speakers are the perfect choice for gardens, backyards, flower beds and any other natural outdoor environment. The new rock inspired enclosures are made of reinforced poly-resin that matches the color of the U.V. weather-resistant lacquer coating that covers the speaker. The result is a stone finish that, even if chipped or marred, will simply expose the same color and texture underneath. This means the speaker will look good and sound good for years to come.

New driver elements and crossover networks have resulted in higher fidelity and greater sound pressure levels. Now the backyard can literally be filled with sound that rivals the finest indoor systems.

Three models of standard coaxial models are available in 5, 6 and 8-inch versions. There is also a dual tweeter model and a dedicated subwoofer with its own amplifier, all of which are available in either granite or sandstone finishes.

If you are looking to provide quality sound outdoors in most any landscape, the new Ruckus series will blend in visually and dramatically impress your customers sonically.

Ruckus 8 One



- 8" Polypropylene Cone Woofer with Sealed Voice Coil, Rubber Surround and Silicone Encased Leads
- ½" Polyamide Dome Tweeter with Silicone Encased Leads, Coaxially Mounted
- Sensitivity: 90dB 1W/1m
- Power Handling: 120 Watts
- Impedance: 8 Ohms
- Frequency Response: 35Hz - 20kHz
- Dimensions: (H x W x D) 11½" x 15¾" x 12¾"
(294 mm x 396 mm x 324 mm)

Ruckus DT 6



- Plays Stereo Sound from One Ruckus Speaker
- 6½" Polypropylene Cone Woofer with Sealed Voice Coils and Silicone Encased Leads
- Two 1" Polyamide Dome Tweeters with Silicone Encased Leads, Coaxially Mounted
- Sensitivity: 91dB 1W/1m
- Power Handling: 80 Watts
- Impedance: 8 Ohms
- Frequency Response: 53Hz - 20kHz
- Dimensions: (H x W x D) 11½" x 16¼" x 13¾"
(292 mm x 413 mm x 349 mm)

Ruckus 6 One



- 6½" Polypropylene Cone Woofer with Sealed Voice Coil, Rubber Surround and Silicone Encased Leads
- ½" Polyamide Dome Tweeter with Silicone Encased Leads, Coaxially Mounted
- Sensitivity: 91dB 1W/1m
- Power Handling: 80 Watts
- Impedance: 8 Ohms
- Frequency Response: 40Hz - 20kHz
- Dimensions: (H x W x D) 9½" x 13" x 10½"
(233 mm x 330 mm x 267 mm)

Ruckus 8 Sub System



- 8" Polypropylene Cone Woofer with Rubber Surround and Silicone Encased Leads
- Specially Tuned Enclosure Provides Outstanding Bass from Very Little Input
- Matches Existing Ruckus Products to Provide More Outdoor Bass
- Includes 250 Watt Powered Amplifier with Dual Voltage Switch, Rack Mount Brackets, and UL, CE & C-Tick Certification for US, Europe, & Australia
- Front-Mounted Volume Control
- Rear-Mounted Low-Pass Crossover & Phase Control
- Sensitivity: 89dB 1W/1m
- Amplifier Output Power: 250 Watts
- Impedance: 6 Ohms
- Frequency Response: 34Hz - 150Hz
- Dimensions: (H x W x D) 18" x 15¾" x 14" (457 mm x 391 mm x 356 mm)
- Amplifier dimensions: (H x W x D) 3½" x 17" x 11½" (89 mm x 432 mm x 292 mm)
- Note: Add ½" height for feet and 4" depth for rear panel connections

Ruckus 5 One



- 5¼" Polypropylene Cone Woofer with Silicone Encased Leads
- ½" Polyamide Dome Tweeter with Silicone Encased Leads, Coaxially Mounted
- Sensitivity: 91dB 1W/1m
- Power Handling: 60 Watts
- Impedance: 8 Ohms
- Frequency Response: 55Hz - 20kHz
- Dimensions: (H x W x D) 8¼" x 12" x 9¾"
(210 mm x 305 mm x 244 mm)

- * All Ruckus Speakers come with Limited LIFETIME Warranty
- * Bass Power 250 Amplifier come with Limited Two year Warranty
- * All Ruckus Speakers available in Gray Granite, Sanstone
- * As we incorporate design improvements, specifications may change without notice

